



SRR60ZS-W/SRC60ZSX-W3

5.6 (1.2 ~ 6.5)

Indoor Unit : SRR60ZS-W

Outdoor Unit : SRC60ZSX-W3

Specifications

R32

Indoor unit			SRR60ZS-W
Outdoor unit			SRC60ZSX-W3
Power source			1Phase, 220 - 240, 50Hz
Nominal cooling capacity (Min~Max)		kW	5.6 (1.2 ~ 6.5)
Nominal heating capacity (Min~Max)		kW	6.7 (1.0 ~ 8.6)
Power consumption	Cooling/Heating	kW	1.70 / 1.89
EER/COP	Cooling/Heating		3.29 / 3.54
Max. running current		A	15
Sound power level	Indoor	Cooling/Heating	60 / 63
	Outdoor	Cooling/Heating	65 / 65
Sound pressure level	Indoor	Cooling (Hi/Me/Lo/Ulo)	44 / 38 / 35 / 30
		Heating (Hi/Me/Lo/Ulo)	45 / 41 / 38 / 33
	Outdoor	Cooling/Heating	52 / 53
Air flow	Indoor	Cooling (Hi/Me/Lo/Ulo)	14.5 / 11.5 / 10.5 / 8.0
		Heating (Hi/Me/Lo/Ulo)	15.0 / 13.0 / 11.5 / 9.0
	Outdoor	Cooling/Heating	39.0 / 33.0
Available external static pressure		Pa	Standard: 5* ¹ (Initial static pressure with air filter: 5Pa)
Exterior Dimensions	Indoor	Height x Width x Depth	mm
	Outdoor		
			640 x 800(+71) x 290
Net weight	Indoor / Outdoor		kg
			24 / 45
Refrigerant	Type/GWP		R32/675
Refrigerant	Charge		kg/TCO ₂ Eq 1.30 / 0.878
Refrigerant piping size	Liquid/Gas		ø inch 6.35(1/4") / 12.7(1/2")
Refrigerant line (one way) length		m	Max. 30
Vertical height differences	Outdoor is higher/lower		m
			Max. 20 / Max.20
Outdoor operating temperature range	Cooling		°C
	Heating		-15~-46
			-15~-24
Bottom air inlet kit (option)			UT-BAT2EF
SEER			6.20
SCOP (Average climate)			4.30
Pdesign (cooling/heating(@-10°C))		kW	5.00/4.50
Annual Electricity Consumption (cooling/heating)		kWh/a	270/1431

- The data is measured under the following conditions(ISO-T1, H1). Cooling: Indoor temp. of 27°CDB, 19°CWB, and outdoor temp. of 35°CDB. Heating: Indoor temp. of 20°CDB, and outdoor temp. of 7°CDB, 6°CWB.
 - Sound level indicates the value in an anechoic chamber. During operation these values are somewhat higher due to ambient conditions.
 - 'tonne(s) of CO₂ equivalent' means a quantity of greenhouse gases- expressed as the product of the weight of the greenhouse gases in metric tonnes and of their global warming potential.
- *1 The maximum external static pressure can be used up to 35Pa (25•35ZS) , 50Pa (50 •60ZS), but the airflow will be reduced.

Schematics

